



Technical Information

Tile & Stone Sealer Selection Chart



<i>Sealer</i>	<i>Aerosol A350</i>	<i>Sealer HPS</i>	<i>Sealer LPS</i>	<i>Coverage *</i>
<i>Substrate</i>	Ideal for Grout Rapid Drying	Porous Substrates Rapid Drying	Dense Substrates Rapid Drying	Per Litre (Approx)
Grout	✓	✓	✓	25 m ²
Porcelain - Polished - Unpolished - Vitrified			✓ ✓ ✓	40 m ²
Marble - Polished - Honed			✓ ✓	20 m ²
Granite - Polished - Honed			✓ ✓	25 m ²
Terrazzo			✓	15 - 20 m ²
Limestone - Polished - Honed		✓	✓ ✓	5 - 20 m ²
Sandstone - Gosford or similar - Bundanoon or similar - Indian or similar		✓ ✓ ✓		5 - 8 m ² 10 m ² 10 - 12 m ²
Travertine		✓		20 m ²
Terracotta		✓		10 to 15 m ²
Pavers		✓	✓	10 m ²
Slate		✓		15 to 20 m ²
Bluestone - Polished - Honed - Rough Sawn		✓ ✓ ✓	✓ ✓ ✓	10 to 15 m ²
Quarry Tile		✓	✓	10 m ²

* Coverage depends on the porosity of the tile or stone being sealed and the method of application. Variation in the coverage to that shown above can occur. The above coverage should be used as a general guide only.